

This Page Is Inserted by IFW Operations  
and is not a part of the Official Record

## **BEST AVAILABLE IMAGES**

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images may include (but are not limited to):

- BLACK BORDERS
- TEXT CUT OFF AT TOP, BOTTOM OR SIDES
- FADED TEXT
- ILLEGIBLE TEXT
- SKEWED/SLANTED IMAGES
- COLORED PHOTOS
- BLACK OR VERY BLACK AND WHITE DARK PHOTOS
- GRAY SCALE DOCUMENTS

**IMAGES ARE BEST AVAILABLE COPY.**

**As rescanning documents *will not* correct images,  
please do not report the images to the  
Image Problem Mailbox.**

# (12) UK Patent Application (19) GB (11) 2 320 299 (13) A

(43) Date of A Publication 17.06.1998

(21) Application No 9725195.3

(22) Date of Filing 01.12.1997

(30) Priority Data

(31) 9625854 (32) 12.12.1996 (33) GB  
9625861 12.12.1996

(71) Applicant(s)

T & N Technology Limited

(Incorporated in the United Kingdom)

Cawston House, Cawston Lane, RUGBY,  
Warwickshire, CV22 7SA, United Kingdom

(72) Inventor(s)

Kenneth James Bunker

(74) Agent and/or Address for Service

P L Drury et al  
T & N Plc, Group Patent Department, Bowdon House,  
Ashburton Road West, Trafford Park, MANCHESTER,  
M17 1RA, United Kingdom

(51) INT CL<sup>6</sup>

F16D 65/12 // F16D 55/36

(52) UK CL (Edition P)

F2E EEK E2N1A17 E2N1A6A E2N1C1 E2N1C3

(56) Documents Cited

GB 2015122 A GB 1350350 A GB 0983548 A  
US 4576255 A

(58) Field of Search

UK CL (Edition P) F2E EDK EEK EJB EJJ  
INT CL<sup>6</sup> F16D 55/00 55/02 55/24 55/26 55/28 55/30  
55/31 55/32 55/33 55/34 55/36 55/38 55/39 55/40  
55/41 55/42 55/44 65/12  
Online:EDOC,WPI

(54) Disc brake system

(57) A disc brake system comprises a rotatable hub 12, and a disc 14, the disc being mounted on the hub for rotation therewith and for sliding movement relative thereto in a direction which is parallel to said central rotational axis 22. The system also comprises a plurality of resilient force applicators which are mounted between the hub 12 and the disc 14, the force applicators acting to apply radially-directed forces to the disc 14 and being distributed circumferentially around the hub 12. As illustrated, there are two slidable discs having teeth 30 which intermesh with splines 28 on the hub, and the force applicators are leaf springs 34. In alternative embodiments, rollers (46, Figs. 3-6) prevent relative rotation of the hub and disc and permit sliding of the disc, and leaf springs (62) may have apertures (66) accommodating the rollers.





Fig. 1


GB 2 320 299

1/4





***Fig. 1***


2/4




*Fig. 2*



4/4



***Fig. 5***



***Fig. 6***

### Disc Brake System

This invention is concerned with a disc brake system, for example for a wheel of a vehicle.

A conventional disc brake system of a vehicle comprises a hub mounted on a suspension link for rotation relative thereto about a central rotational axis. The hub provides a mounting for the wheel. The system also comprises a brake disc mounted on the hub to rotate therewith, friction material pads arranged on opposite sides of the disc, and at least one piston and cylinder assembly operable to urge the pads into engagement with the disc, to brake the hub and hence the wheel. Conventionally, the piston and cylinder assembly is slidably mounted on a slide bolted to the suspension link of the vehicle. The disc is conventionally rigidly fixed to the hub, and wear of the pads and/or the disc is accommodated by the sliding movement of the cylinder.

Disc brake systems which have discs which are non-rotational relative to the hub but slidable on the hub by means of splines or other non-circularity of the hub and the disc are also known, see, for example, GB 1 396 503. However, such systems are associated with technical problems. For example, since the discs are relatively thin, they tend to tilt on the hub and affect the braking ability. Also, there is a tendency for noise to be produced by rattle of the disc against the hub. At higher disc temperatures, these problems can be particularly severe since, when there is a large temperature differential, such as 600°C, between the braking surface of

the disc and the hub, the disc expands considerably, away from the hub, exacerbating the problems of tilting and rattle.

The present invention addresses these technical problems.

According to the present invention, there is provided a disc brake system comprising a hub, and a disc, the hub being mounted for rotation about a central rotational axis and the disc being mounted on the hub to rotate therewith, wherein the disc is slidable on the hub in a direction which is parallel to said central rotational axis, wherein the system also comprises a plurality of resilient force applicators which are mounted between the hub and the disc, the force applicators acting to apply radially-directed forces to the disc, the force applicators being distributed circumferentially around the hub.

In a disc brake system according to the invention, the forces applied by the resilient force applicators serve to reduce noise from rattle of the disc against the hub, to control the sliding movement of the disc on the hub, to control the concentricity of the disc with the hub, and to provide stability of the disc to avoid tipping. In order to reduce disc wear, a disc brake system according to the invention may have two or more discs mounted side-by-side on the same hub, the resilient force applicators acting on all the discs.

Preferably, in order to achieve improved concentricity of the disc on the hub, the resilient force applicators are substantially equispaced about said central rotational axis. There may be at least three equally-spaced resilient force applicators.

Preferably, the force applicators are leaf springs.



Each leaf spring may be secured to the outer surface of the hub in a manner such that the spring extends tangentially of the hub when the disc is not mounted on the hub.

In one possibility, the hub and the disc have intermeshing surface features which prevent relative rotational movement between the hub and the disc but allow relative movement parallel to the central rotational axis, there being spaces between said intermeshing surface features in which said force applicators are mounted. Said intermeshing surface features may comprise axially-extending splines on the external surface of the hub and teeth projecting from the internal surface of the disc.

In another possibility which reduces wear problems where the hub and the disc engage one another and difficulties in manufacturing intermeshing surface features, the internal surface of the disc and the external surface of the hub are formed with recesses in which a plurality of axially-extending rollers are captive, the rollers serving to transmit rotational drive between the hub and the disc, the disc being slidable axially on the rollers and hence relative to the hub. It is known from GB 983 548 to transmit driving force between the hub and the disc by means of axially-extending rollers which are captive between the hub and the disc. In this case, the leaf springs may be positioned between the rollers around the hub. Alternatively, at least some of the leaf springs may have an opening therein in which one of the rollers is received. Preferably, in order to reduce corrosion problems, the rollers have surfaces formed from a material of higher corrosion-resistance than steel, eg nickel-chrome.

There now follow detailed descriptions, to be read with reference to the accompanying drawings, of three disc

brake systems which are illustrative of the present invention.

In the drawings:

Figure 1 is a front elevation of the first illustrative system;

Figure 2 is a cross-section of the first illustrative system taken on the broken line A-A in Figure 1;

Figure 3 is a front elevation of the second illustrative system;

Figure 4 is a cross-section of the system of the second illustrative system taken on the broken line A-A in Figure 3;

Figure 5 is a perspective view of a roller and a leaf spring which form a part of the third illustrative system; and

Figure 6 is a front elevation of part of the third illustrative system showing the roller and spring shown in Figure 5.

The first illustrative disc brake system 10 shown in Figures 1 and 2 is for a wheel of a car. The system 10 comprises a hub 12, on which the wheel can be mounted, and two annular brake discs 14. The hub 12 is mounted for rotation about a central rotational axis 22 and the discs 14 are mounted parallel to one another on the hub 12 to rotate therewith. The discs 14 are, however, slidable on the hub 12 in a direction which is parallel to the axis 22. The system 10 also comprises four friction pads 16 (Figure 2) for braking the discs 14 by engaging side surfaces of the discs. The friction pads 16 are secured to three backing plates 18, one backing plate 18a being between the discs 14 and the others being on opposite sides of the discs 14 to the plate 18a. The median plate 18a has friction pads 16 secured to both of its faces. The brake pads 16 and the backing plates 18 are not shown in Figure 1.

In order to prevent relative rotational movement between the hub 12 and the discs 14 but allow relative movement parallel to the central rotational axis 22, the hub and the discs have intermeshing surface features. Specifically, the hub 12 has axially-extending splines 28 formed on its external surface on which the discs 14 are mounted. The splines 28 are arranged in groups so that three 75° arcs 24 of the outer surface of the hub 12 have the splines 28, the arcs 24 being separated by three 45° arcs 26 which are free of splines and are spaced from the discs 14. The splines 28 engage inwardly-projecting teeth 30 on corresponding arcs 32 of the internal surfaces of the discs 14, in sliding axial engagement.

The system 10 also comprises a plurality of resilient force applicators which are mounted between the hub 12 and the discs 14. These force applicators are provided by three leaf springs 34 distributed circumferentially around the hub 12. One of the leaf springs 34 is secured to each of the splinless arcs 26 of the hub 12. The leaf springs 34 are, thus, equispaced about the central rotational axis 22. Each leaf spring 34 is secured in the circumferential centre of the portion 26 of the outer surface of the hub 12 to which it is secured, so that the spring 34 extends tangentially of the hub 12 when the disc 14 is not mounted on the hub 12. However, the springs 34 are deformed by the presence of the discs 14 so that each press resiliently on the on the discs 14 at the circumferential ends of the springs 34. The leaf springs 34 are generally rectangular pieces of spring steel, and are 0.25 - 0.3mm thick. The leaf springs 34 are each secured to the hub 12 by a central screw 36. In alternative embodiments, there may be more than three leaf springs 34. The springs 34 act to apply radially-directed forces to the discs 14.

In alternative embodiments, the leaf springs 34 have a projection which is clipped into a socket in the hub 12 in order to secure the springs to the hub.

When the disc brake system 10 is mounted in a vehicle, one of the two outer backing plates 18 is fixedly mounted, the other outer backing plate 18 and the median backing plate 18a are mounted to slide in a direction which is parallel to the axis 22. In order to brake the vehicle, the movable outer backing plate 18 is moved towards the discs 14 so that its pad 16 presses on the adjacent disc 14. This causes this disc 14 to slide on the hub 12 so that the disc presses on one of the pads 16 of the median backing plate 18a. This causes the median backing plate 18a to slide on the hub 12 so that its other pad 16 presses on the other disc 14. This causes the other disc 14 to slide on the hub 12 until it presses against the pad 16 of the fixed backing plate 18. Frictional forces between the pads 16 and the discs 14 then brake the hub 12 and hence the wheel attached thereto. During the sliding movement of the discs 14, the forces applied by the leaf springs 34 control the movement, maintain the disc concentric relative to the axis 22, prevent tilting, and prevent rattling.

The second illustrative disc brake system 40 shown in Figures 3 and 4 is generally similar to the system 10 except as hereinafter described and the same reference numerals are used for similar parts. The system 40 comprises a hub 12, and two brake discs 14. The hub 12 is mounted for rotation about a central rotational axis 22 and the discs 14 are mounted parallel to one another on the hub 12 to rotate therewith. The discs 14 are, however, slidable on the hub 12 in a direction which is parallel to the axis 22.

The system 40 differs from the system 10 in the design of its hub 12, in the form of the connection between its

hub 12 and its discs 14, and in having four force applicators in the form of leaf springs 34 mounted on the hub 12 by screws 36, instead of three. Specifically, the splines 28 and teeth 30 of the system 10 are not present. Instead, the internal surface of each disc 14 is formed with four concave recesses 42 therein which are equispaced about the axis 22, the recesses 42 being generally semi-circular in transverse cross-section, and the external surface of the hub 12 is formed with four corresponding concave recesses 44 which are arranged so that each recess 44 can co-operate with one of the recesses 42 in forming a cylindrical space.

The system 40 also comprises four axially-extending cylindrical rollers 46 made of nickel-chrome. The rollers 46 are captive between the disc discs 14 and the hub 12. Each roller 46 is received the cylindrical spaces formed by one of the recesses 44 of the hub 12 and by two of the recesses 42, one in each disc 14. The rollers 46 are, thus, equispaced about the central rotational axis 22. The discs 14 are in axial sliding engagement with the rollers 46 and can slide axially relative to the hub 12. The rollers 46 transmit rotational drive between the hub 12 and the discs 14.

The four leaf springs 34 of the system 40 are secured by the screws 36 to the circumferential centres of portions 48 of the external surface of the hub 12 which are between the rollers 46. Each spring 34 extends tangentially of the hub 12 when the discs 14 are not mounted on the hub 12 but are bent when the discs 14 are mounted on the hub 12 so that they act to apply radially-directed forces to the discs 14. Only one of the leaf springs 34 is shown in Figures 3 and 4.

The third illustrative disc brake system 60, illustrated by Figures 5 and 6 is similar to the system 40

except as described below and like reference numerals are used for like parts. The system 60 comprises a hub 12 and two discs 14 (only one disc 14 is shown). The hub 12 and the discs 14 have recesses 42 and 44, respectively, in which rollers 46 are received. The system 60 differs from the system 40, however, in that its force applicators are provided by four leaf springs 62 of different design to the springs 34 and positioned differently.

Each of the leaf springs 62 is made from sheet spring steel which is 0.25 - 0.3mm thick and is generally rectangular except for tabs 64 which are bent over the ends of the hub 12 to secure the spring 62 to the hub. Each spring 62 is positioned over one of the rollers 46 with the roller 46 received in an opening 66 through the spring 62.

## CLAIMS

- 1 A disc brake system comprising a hub, and a disc, the hub being mounted for rotation about a central rotational axis and the disc being mounted on the hub to rotate therewith, wherein the disc is slidable on the hub in a direction which is parallel to said central rotational axis, wherein the system also comprises a plurality of resilient force applicators which are mounted between the hub and the disc, the force applicators acting to apply radially-directed forces to the disc, the force applicators being distributed circumferentially around the hub.
- 2 A disc brake system according to claim 1, wherein the resilient force applicators are substantially equispaced about said central rotational axis.
- 3 A disc brake system according to either one of claims 1 and 2, wherein the force applicators are leaf springs.
- 4 A disc brake system according to any one of claims 1 to 3, wherein each leaf spring is secured to the outer surface of the hub in a manner such that the spring extends tangentially of the hub when the disc is not mounted on the hub.
- 5 A disc brake system according to any one of claims 1 to 4, wherein the hub and the disc have intermeshing surface features which prevent relative rotational movement between the hub and the disc but allow relative movement parallel to the central rotational axis, there being spaces between said intermeshing

surface features in which said force applicators are mounted.

- 6 A disc brake system according to claim 5, wherein said intermeshing surface features comprise axially-extending splines on the external surface of the hub and teeth projecting from the internal surface of the disc.
- 7 A disc brake system according to any one of claims 1 to 4, wherein the internal surface of the disc and the external surface of the hub are formed with recesses in which a plurality of axially-extending rollers are captive, the rollers serving to transmit rotational drive between the hub and the disc, the disc being slidable axially on the rollers and hence relative to the hub.
- 8 A disc brake system according to claim 7, wherein the leaf springs are positioned between the rollers around the hub.
- 9 A disc brake system according to claim 7, wherein at least some of the leaf springs have an opening therein in which one of the rollers is received.
- 10 A disc brake system according to any one of claims 7 to 9, wherein the rollers have surfaces formed from a material of higher corrosion-resistance than steel.
- 11 A disc brake system substantially as hereinbefore described with reference to, and as shown in, Figures 1 and 2, or Figures 3 and 4, or Figures 5 and 6 of the accompanying drawings.